

Technical information

ULTIPATCH *LINEMASTER*



DESCRIPTION

Ultipatch Linemaster is a durable, quick drying paint for use with stencils, line marking equipment or for free hand applications.

Ultipatch Linemaster can be used on car parks, within factories, for road marking, highway maintenance, tennis courts and any other sports surfaces, playgrounds, warehouse layouts, hazard warnings, surveying and surfaces identification of underground services.

SPECIAL PROPERTIES

- Rapid drying
- Easy to use
- Available in yellow, blue, red and white
- Supplied in 750mm cans

PREPARATION

All application substrates must be sound, clean and free from dust, dirt, debris, oil, grease and other contaminants.

APPLICATION INSTRUCTIONS

Shake can vigorously until the agitator ball rattles and then shake for a further 1-2 minutes. Invert the aerosol and fasten into the adapter. The can may also be hand held.

If the nozzle becomes blocked during use, remove aerosol from applicator, stand upright and repeatedly depress nozzle until it clears.

Ultipatch Linemaster dries in approximately 30 minutes where it can withstand light traffic. The paint is fully curing in 24 hours.

CLEAN UP

Paint spillages should be cleaned up as soon as possible. Cleaning of tools and equipment should be carried out as soon as is practicable well away from the application area.

QUALITY CONTROL

All Pozament products are factory blended, tested and packaged to quality control procedures in accordance with BS EN ISO 9001.

PACKAGING AND STORAGE

Ultipatch Linemaster is available in boxes of 12 x 750ml cans. Ultipatch Linemaster should be stored in cool, dry, frost free areas out of direct sunlight. The product should be used on a first in – first out basis.

Shelf life is 12 months' subject to temperature and humidity. Individual cans should be stored in sealed original packaging in a dry location at temperatures between 5°C and 50°C. Avoid exposure to water, frost or heat - high temperatures and high humidity will lead to a reduced shelf life.

HEALTH AND SAFETY

Health and safety advice, which must be followed, can be found on the Material Safety Data Sheet.

INFORMATION, PRICES & ORDERING

For technical information, pricing and to place orders contact our Sales Office on the following:

Telephone: 03444 630 046

Email: specialistproducts@tarmacbp.co.uk

Visit our website: www.tarmac.com

Tarmac Building Products Ltd.,
Swains Park Industrial Estate, Park Road, Overseal,
Swadlincote, Derbyshire, DE12 6JT



The information supplied in our literature or given by our employees is based upon extensive knowledge and experience. This information, together with that supplied by our agents or distributors, is given in good faith in order to help you. Our Company policy is one of continuous Research and Development; we therefore reserve the right to update this information at any time without prior notice. We also guarantee the consistent high quality of our products; however, as we have no control over site conditions or the execution of the work, we accept no liability for any loss or damage which may arise as a result thereof. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may affect specific installation recommendations. Any existing intellectual property right must be observed. Tarmac's standard terms and conditions apply.

For more details contact:

03444 630 046

specialistproducts@tarmacbp.co.uk

Product Data Sheet