



ULTIPAVE

The ultimate Clause 942 BBA HAPAS approved road surface solution

AVAILABLE WITH
ULTILOW
TECHNOLOGY



T3 Tarmac Ground Floor T3 Trinity Park
Bickenhill Lane Birmingham B37 7ES

TARMAC.COM



ULTIPAVE

The ultimate Clause 942 BBA HAPAS approved road surface solution

ULTIPAVE is a high performance asphalt suitable for most locations, from rural roads to heavily trafficked motorways. Using high grade aggregates it delivers outstanding durability along with impressive reductions in road noise and surface spray.



To find your local Tarmac office visit: [tarmac.com/contact](https://www.tarmac.com/contact)

ULTIMATE LONG TERM DURABILITY

Using high quality high PSV aggregates, it maintains its surface texture and skid resisting properties over prolonged periods, even on heavily trafficked routes.

EXCEPTIONAL CONTROL

Our stringent quality control processes, from design to laying, ensure exceptional control over the quality and consistency of finished asphalt surfaces.

PROVEN PERFORMANCE

An exceptional record of performance on some of the busiest motorway routes in the UK.

ULTIMATE VERSATILITY

The ULTIIPAVE range includes 6mm, 10mm and 14mm products to meet a variety of thickness and texture requirements.

ULTIMATE QUALITY

Our third party accredited ISO 9001 Systems and BBA certification ensures a consistently high quality product is supplied at all times.

ULTIPAVE D

Also available is a 10mm dense version, designed to deliver a lower texture, denser formulation than standard 10mm ULTIIPAVE and resist pavement deformation and premature wear on heavily trafficked roundabouts.

ULTIMATE SUPPORT

At Tarmac, technical excellence comes as standard. ULTIIFLEX is only available for installation by accredited contractors who have full access to our expert training, advice and technical support or by our own expert Contracting division. This ensures it is laid to the highest industry standards.



TECHNICAL DATA

The table below contains test results showing performance compared to conventional asphalt products.

ULTIDRIVE	Typical Air Voids	Typical Stiffness (ITSM)	Typical Water Sensitivity (ITSR)	Typical Wheel Tracking	
				WTSAIR	PRDAIR
Standard	BS EN 12697-8	BS EN 12697-26	BS EN 12697-12	BS EN 12697-22 (Proc. B at 60°C)	
ULTIPAVE 6MM	3.5%	3400MPa	85%	0.18mm/10 ³ load cycles	9.6%
ULTIPAVE D 10MM	3.0%	4000MPa	86%	0.16mm/10 ³ load cycles	9.2%
ULTIPAVE 10MM	4.0%	3400MPa	84%	0.19mm/10 ³ load cycles	10.0%
ULTIPAVE 14MM	3.5%	3500MPa	86%	0.16mm/10 ³ load cycles	8.8%