

Declaration of Performance DoP No. 001

1. Unique identification code of product type: **Prescribed General Purpose Masonry Mortar.**
2. Type, batch or serial number or any other element allowing identification of the construction product: **The date of production can be traced via the date printed on the bag.**
3. Intended use: **Prescribed general purpose masonry mortar for external use in elements subject to structural requirements.**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer:-
Tarmac Building Products Limited, i10, Railway Drive, Wolverhampton, WV1 1LH
5. Authorised representative: **Not applicable**
6. Assessment and verification of constancy of performance: **System 4**
7. In accordance with the harmonised standard **EN 998-2:2010.**

8. Declared performance

Unique Identification Code	KCTA1353L KCTA008CF	KCZZ107IK	KMUC136XX	PLUC001R1724	PLUC005R1726	Harmonised technical specification
Product Name	Multi-purpose mortar	Mix-in-the-bag GP mortar mix	U-Can Pointing Repair Mortar	U-can Brick and Wall Mortar	U-can Render Repair Mortar	
Essential Characteristics	Performance					EN 998-2:2010
Proportion of constituents (by weight)						
Cement (declared)	15%	15%	15%	15%	15%	
Aggregates (declared)	85%	85%	85%	85%	85%	
Initial shear strength (tabulated)	0.15 N/mm²	0.15 N/mm²	0.15 N/mm²	0.15 N/mm²	0.15 N/mm²	
Water absorption (declared)	0.8 kg/(m²·min^{0.5})	0.8 kg/(m²·min^{0.5})	0.8 kg/(m²·min^{0.5})	0.8 kg/(m²·min^{0.5})	0.8 kg/(m²·min^{0.5})	
Water vapour permeability (tabulated)	<i>μ</i> _{15/35}	<i>μ</i> _{15/35}	<i>μ</i> _{15/35}	<i>μ</i> _{15/35}	<i>μ</i> _{15/35}	
Reaction to fire (class)	Euroclass A1	Euroclass A1	Euroclass A1	Euroclass A1	Euroclass A1	
Chloride content (declared)	0.05 % Cl	0.05 % Cl	0.05 % Cl	0.05 % Cl	0.05 % Cl	
Durability against freeze/thaw	Evaluation based on provisions valid in the intended place of use of the mortar					

Table 1

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: Mr
Stuart Allerton – (Quality Systems Manager)



18th August 2014

DoP No. 001

Issue date 18th August 2014