

Declaration of Performance

DoP No. 031

1. Unique identification code of product type: **See Table 1 below.**
2. Type, batch or serial number or any other element allowing identification of the construction product: **The date of production can be traced via the date printed on the despatch note.**
3. Intended use: **General purpose rendering mortar (GP) for internal and external use in wall, column, partition and ceiling finishes.**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer:- **Tarmac Building Products Limited, i10, Railway Drive, Wolverhampton, WV1 1LH**
5. Authorised representative: **Not applicable**
6. Assessment and verification of constancy of performance: **System 4**
7. In accordance with the harmonised standard **EN 998-1:2010**

8. Declared performance

Unique Identification Code	GP-CSIIW0 RTU RENDER	GP-CSIII- W0 RTU RENDER	GP-CSIV- W0 RTU RENDER	GP-CSII-W0 RTU RENDER WP	GP-CSIII-W0 RTU RENDER WP	GP-CSIV-W0 RTU RENDER WP	Harmonised technical specification
Essential Characteristics	Performance						
Reaction to fire (class)	A1	A1	A1	A1	A1	A1	EN 998- 1:2010
Adhesive Strength (declared)	0.5 N/mm ² FP: B	0.5 N/mm ² FP: B	0.2 N/mm ² FP: B	0.5 N/mm ² FP: B	0.4 N/mm ² FP: B	0.6 N/mm ² FP: B	
Compressive strength (category)	CS II	CS III	CS IV	CS II	CS III	CS IV	
Capillary water absorption (category)	W0	W0	W0	W0	W0	W0	
Water Vapour Permeability coefficient μ (declared)	15/35	15/35	15/35	15/35	15/35	15/35	
Durability	Evaluation based on provisions valid in the intended place of use of the mortar						

Table 1

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Signed for and on behalf of the manufacturer by: Mr
Stuart Allerton – (Quality Systems Manager)



18th August 2014