

Declaration of Performance DoP No. 036

1. Unique identification code of product type: **Pozament Rapid Set Adhesive C1F.**
2. Type, batch or serial number or any other element allowing identification of the construction product: **The date of production and batch number are printed on the packaging.**
3. Intended use: **Fast setting cementitious adhesive for tiling**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer:-
Tarmac Building Products Limited, i10, Railway Drive, Wolverhampton, WV1 1LH
5. Authorised representative: **Not applicable**
6. Assessment and verification of constancy of performance: **System 3**
7. In accordance with the harmonised standard **EN 12004:2007**. Initial type testing has been carried out by Lucideon Limited, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, notified body number NB1289.

8. Declared performance

Essential Characteristics	Performance	Harmonised technical specification
Early tensile adhesion strength after not more than 6h (declared)	≥ 0,5 N/mm ²	EN 12004:2007
Initial tensile adhesion strength (declared)	≥ 0,5 N/mm ²	
Tensile adhesion strength after heat ageing (declared)	≥ 0,5 N/mm ²	
Tensile adhesion strength after water Immersion (declared)	≥ 0,5 N/mm ²	
Tensile adhesion strength after freeze/thaw cycles (declared)	≥ 0,5 N/mm ²	
Open time: tensile adhesion strength after not more than 10 min (declared)	≥ 0,5 N/mm ²	
Reaction to fire (class)	A1	

Table 1

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Mr Stuart Allerton – (Quality Systems Manager)



18th August 2014