

## Declaration of Performance DoP No. 048

1. Unique identification code of product type: See Table 1 below.

2. Type, batch or serial number or any other element allowing identification of the construction product: The date of production that can be used for traceability is printed either on the packs of bricks or on the delivery note

3. Intended use: In walls, columns and partitions

4. Name, registered trade name or registered trademark and contact address of the manufacturer: Tarmac Building Products, i10, Railway Drive, Wolverhampton, WV1 1LH

5. Authorised representative: Not applicable

6. Assessment and verification of constancy of performance: System 4

7. In accordance with the harmonised standard EN 771-3:2011 +A1 2015

8. European Technical Assessment: Not applicable



## Declaration of Performance DoP No. 048

## 9. Table 1 Declared performance

| Product/Unique Identification Code              | 22.5N Topcrete Bricks   | 10.4N Hemelite Bricks  |
|---|---|--|
| Harmonised Technical Specification              | EN 771-3:2011 + A1 2015   |  |
| Essential Requirement                           | Declared performance  |  |
| Dimensions (mm)                                 | 215 x (100, 140mm) x 65mm                                       | 215 x (100, 140mm) x 65mm  |
| Dimensional tolerances                          |   |  |
| Category  | D1  | D1   |
| Flatness  | NPD   | NPD  |
| Plane parallelism                               | NPD   | NPD  |
| Configuration to EN 1996-1-1                    | Group1  | Group1   |
| Compressive Strength N/mm <sup>2</sup> (Cat II) | 22.5  | 10.4   |
| Dimensional stability (mm/m)                    | NPD   | NPD  |
| Reaction to fire                                | Euroclass A1  | Euroclass A1   |
| Shear bond strength N/mm <sup>2</sup>           | 0.15  | 0.15   |
| Flexural bond strength N/mm <sup>2</sup>        | NPD   | NPD  |
| Gross dry density kg/m <sup>3</sup>             | 1950  | 1600   |
| Water vapour diffusion coefficient              | 5/15  | 5/15   |
| Water absorption g/m <sup>2</sup> s             | NPD - Not to be left exposed                                    | NPD - Not to be left exposed   |
| Thermal conductivity, W/mK (λ10, dry)           | 0.95  | 0.60   |
| Durability Against Freeze-Thaw                  | NPD – Not to be left exposed                                    | NPD – Not to be left exposed   |
| Dangerous Substances                            | Information on dangerous substances will only be given when and | where required and in the appropriate form. See Annex ZA.3 of EN 771-3 |



## Declaration of Performance DoP No. 048

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf Tarmac Building Products:

Chris Mason Manufacturing Management & Information Systems Manager

de