

## Declaration of Performance DoP No. 050

1. Unique identification code of product type: **Pozament Extended Set Flexible Adhesive C2TE S1.**
2. Type, batch or serial number or any other element allowing identification of the construction product: **The date of production and batch number are printed on the packaging.**
3. Intended use: **Improved deformable cementitious adhesive with reduced slip and extended open time for tiling.**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer:-  
**Tarmac Building Products Limited, i10, Railway Drive, Wolverhampton, WV1 1LH**
5. Authorised representative: **Not applicable**
6. Assessment and verification of constancy of performance: **System 3**
7. In accordance with the harmonised standard **EN 12004:2007**. Initial type testing has been carried out by Lucideon Limited, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, notified body number NB1289.

8. Declared performance

| Essential Characteristics   | Performance               | Harmonised technical specification |
|---|---------------------------|------------------------------------|
| Initial tensile adhesion strength (declared)  | $\geq 1 \text{ N/mm}^2$   | EN 12004:2007                      |
| Tensile adhesion strength after heat ageing (declared)                              | $\geq 1 \text{ N/mm}^2$   |                                    |
| Tensile adhesion strength after water Immersion (declared)                          | $\geq 1 \text{ N/mm}^2$   |                                    |
| Tensile adhesion strength after freeze/thaw cycles (declared)                       | $\geq 1 \text{ N/mm}^2$   |                                    |
| Extended open time: tensile adhesion strength after not less than 30 min (declared) | $\geq 0,5 \text{ N/mm}^2$ |                                    |
| Slip (declared)   | $\leq 0,5 \text{ mm}$     |                                    |
| Transverse deformation (declared)   | $\geq 2,5 \text{ mm}$     |                                    |
| Reaction to fire (class)  | E                         | Commission Decision 2010/81 /EU    |

Table 1

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Mr Stuart Allerton – (Quality Systems Manager)



5<sup>th</sup> September 2014