

## Declaration of Performance DoP No. 054

- 1. Unique identification code of product type: 126P402
- Type, batch or serial number or any other element allowing identification of the construction product:
   14/20MM COATED CHIPPING 40/60 PSV 65
- 3. Intended use: Hot Rolled Asphalt
  - 4. Name, registered trade name or registered trade mark and contact address of the manufacturer:-i10, Railway Drive, Wolverhampton, WV1 1LH
- 5. Authorised representative: Not applicable
- 6. Assessment and verification of constancy of performance: BSI Ltd, notified FPC certification body No. 0086, performed the initial inspection of the manufacturing plant and of FPC and the continuous surveillance, assessment and evaluation of FPC and issued the certificate of conformity of the FPC No. 0086CPD532227/0086CPD538824.
- 7. In accordance with the harmonised standard BS EN 13108:4

8. Declared performance

·	Essential	Characteristic	CS	
Adhesion of binder to aggregate     Stiffness     Resistance to permanent deformation  Essential Characteristics	4. Resistance to fatigue 5. Skid resistance 6. Resistance to abrasion		7. Reaction to fire stances 8. Dangerous su 9. Durability  Performance	
		T		
		31.5mm		100%
		20mm		95%
2, 3, 5, 6	Grading	14mm		10%
		10mm		2%
		0.063mm		1.0%
1,2,3,4,5,6	Binder Content		NPD	
1,2,4,5	Void Content Minimum			NPD
1	Maximum Water Sensitivity		NPD NPD	
	-			
2	Stiffness Minimum			NPD
		Maximum		NPD
3	Maximum wheel tracking rate	Small device		NPD
3	Maximum rut depth	Small device		NPD
7	Reaction to Fire			NPD
8	Dangerous substances			NPD
9	Binder Volume			NPD
9	Resistance to Fuel			NPD
9	Resistance to de-icing fluid			NPD

Table 1

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Mr Stuart Allerton – (Quality Systems Manager)

1. Bleeta

27<sup>th</sup> April 2015